PIG TAILS INFORMATION

All pig tails are supplied with sleeve for identifying the cable, to improve the case of assembly.


Photoelectric sensors



Proximity switch



Valve connector



Other products
On request

MINI-STYLE 7/8"-16UN 2~5PINS



MICRO-STYLE 1/2"-20UN 3~5PINS



EURO-STYLE M12X1 3~5PINS



PICO-STYLE M8X1 3~4PINS



PIG TAILS MODEL NUMBERING SCHEME

Pig tails model numbering scheme

1. Standard cable diameter for proximity switch

M30

- ø**5**.8

M12 - Ø4

standard cable lengths for proximity switch 0.3M, 0.6M, 1.0M, 1.5M AND 2.0M.

2. Standard cable diameter for valve connector

Ø5 Ø5.5 Ø6

standard cable lengths for valve connector

2M, 3M AND 5M

3. Standard cable diameter for photo electric sensor

φ3(3X0.5) φ5(4X0.5)

Standard cable lengths for photo electric sensor 6 (150MM), 0.5M, 2M, AND 9M

- 4. Other cable lengths or cable diameter on request
- 5. Selection guid

① ② ③ ④ ⑤ E S 3—5.0 × 1.0

1. Style

N= MINI Series 7/8"-16UN M= MICRO Series 1/2"-20UNF

E(H)= EURO Series Thick Style, M12x1

Ø5.8(4X0.5)

E(B)= EURO Series thin Style, M12x1 P= PICO Series M8x1











2. Shape





3. Pins

2









4.Cable diameter

φ2.5 φ3 φ3 φ4 φ5 φ5.5 φ5.8 φ6

5.Cable diameter

150MM 0.3M 0.5M 0.6M 1.0M 1.5M 2.0M 3.0M 5.0M 9.0M